

Modular Linear Cable Engine

Our linear cable engines are designed to be used in the laying and retrieval of subsea cables used within such industries as the power industry and telecommunication industry. They are powered by a hydraulic powerpack and controlled with a remote ergonomically designed control desk. It is of robust design and is suitable to be operated in the most hazardous environments the industry has to offer. These rigs have been designed to attach together to give any size rig up to a 24 pair LCE.



Key Features:

- Maximum Dynamic Pull tension 6Te*;
- Max speed in excess of 3m/s;
- Suitable for cable sizes up to 300mm;
- Pass objects up to 400mm;
- Self contained control desk;
- Digital readouts for cable tension, speed, distance;
- Powered by HPU (supplied);
- In emergency, or power loss situations, the wheel pairs will automatically close and can hold the product for over 1 hour;
- Simple deck installation with removable feet;
- Can be modularly attached to further machines in our fleet to give up to a 24 pair LCE.

*Please note that the maximum tension achievable will depend upon the type and size of cable due to friction factor limitations, and the general lay conditions.

Basic Specifications:

Dimensions:	LCE Dependent
Control Modes:	Auto, Manual, and Render
Typical HPU Supplied:	Rig 15 (75kW Closed Loop HPU)
Power Requirements:	HPU Dependent
Length of hoses/data cable between LCE and HPU:	10m (If required this can be lengthened)
Length of data cable between LCE and control desk:	15m (If required this can be lengthened)
Tension Readout Accuracy:	Usually within 5% (on site calibration required)
Bridge Readout Capability:	On request



FHP Ltd, Unit BT 96/4,
Fisher Industrial Estate, Fisher Street, Walker,
Newcastle upon Tyne, NE6 4LT

Tel: 0191 2637272 Fax: 0191 2634016

Web: www.fhpltd.co.uk

Registered in England No. 02044252.