

Rig 12: 82kW Open Loop HPU

This 82kW open loop HPU can is mainly used to flush a wide range of hydraulic equipment. It is of robust design and is suitable to be operated in the most hazardous environments the industry has to offer. It is capable of supplying up to 450L/min of flow, and has a maximum operating pressure of 135 Bar. The system has an air blast cooler to keep the oil within its optimum working temperature, even in the hottest of climates.

Key Features:

- Max. flow rate of 450L/min;
- Max. pressure is 135 bar;
- Air blast cooler built in;
- Versatile rig open to many applications;
- Suitable for a variety of oils;
- Fitted with pressure, and return filtration units;
- Locally operated;



Basic Specifications:

Height:	2100mm
Width:	1800mm
Length:	3200mm
Weight:	3.75Te
Motor Power:	82kW
Voltage/Current Required:	415V/140A
Pump Max. Pressure	135 Bar
Pump Max. Flow	450L/min @ 1500RPM (50Hz Supply)



**FHP Ltd, Unit BT 96/4,
Fisher Industrial Estate, Fisher Street, Walker,
Newcastle upon Tyne, NE6 4LT**

Tel: 0191 2637272 Fax: 0191 2634016

Web: www.fhpltd.co.uk

Registered in England No. 02044252.