

**Rig 15: 75kW Closed Loop HPU**

This compact 75kW closed loop HPU is usually used to power and operate one of our fleet of linear cable engines, however with little modification it can also be used in conjunction with other rigs such as constant tension winches. It is of robust design and is suitable to be operated in the most hazardous environments the industry has to offer. It is capable of supplying up to 200L/min of flow from its main pump, which has a maximum operating pressure of 350 Bar, and 52L/min of flow from an auxiliary pump, which has a maximum operating pressure of 190 Bar. The system has an air blast cooler to keep the oil within its optimum working temperature, even in the hottest of climates.

**Key Features:**

- Main pump has a max. flow rate of 200L/min;
- Main pump's max. pressure is 350 bar;
- Aux. pump has a max. flow rate of 52L/min;
- Aux. pump's max. pressure is 190 bar;
- Air blast cooler built in;
- Versatile rig open to many applications;
- Remote proportional flow control;
- Remote proportional pressure control;
- Suitable for a variety of oils;
- Fitted with aux. pressure, boost, and return filtration units;
- Onboard system health monitoring, including oil temperature, level and filter condition monitoring;
- Compact and robust design.



**Basic Specifications:**

Height:	1.9m
Width:	1.4m
Length:	2.0m
Weight:	3.2Te
Motor Power:	75kW
Voltage/Current Required:	415V/125A
Main Pump Max. Pressure	350 Bar
Main Pump Max. Flow	166L/min @ 1500RPM (50Hz Supply) 200L/min @ 1800RPM (60Hz Supply)
Auxiliary Pump Max. Pressure	190 Bar
Auxiliary Pump Max. Flow	45L/min @ 1500RPM (50Hz Supply) 52L/min @ 1800RPM (60Hz Supply)



FHP Ltd, Unit BT 96/4,  
Fisher Industrial Estate, Fisher Street, Walker,  
Newcastle upon Tyne, NE6 4LT

Tel: 0191 2637272 Fax: 0191 2634016

Web: [www.fhpltd.co.uk](http://www.fhpltd.co.uk)