

Rig 44: Electric 2 Pair Cable Transporter

Our Electric 2 pair cable transporter, Rig 44, is designed to be used in the transportation of cables used within such industries as the power industry and telecommunication industry. It is a standalone unit which is controlled with a remote ergonomically designed pendant. It is of robust design and is suitable to be operated in the most hazardous environments the industry has to offer.

Key Features:

- Maximum Dynamic Pull tension 1.4Te*;
- Max speed in excess of 3m/s;
- Suitable for cable sizes up to 300mm;
- Pass objects up to 400mm;
- Self contained control pendant;
- Simple deck installation;
- In emergency, or power loss situations, the wheel pairs will automatically close and can hold the product for over 1 hour;

Please note that the maximum tension achievable will depend upon the type and size of cable due to friction factor limitations, and the general lay conditions.



Basic Specifications:

Height:	2.0m
Width:	1.9m
Length:	2.5m
Weight:	4.3 Te
Control Modes:	Manual
Power Requirements:	425V/63A
Length of data cable between LCE and control pendant:	5m



FHP Ltd, Unit BT 96/4,
Fisher Industrial Estate, Fisher Street, Walker,
Newcastle upon Tyne, NE6 4LT

Tel: 0191 2637272 Fax: 0191 2634016

Web: www.fhpltd.co.uk

Registered in England No. 02044252.